

T8.4



LED TUBE

- Rated life of 50,000+ hours
- Operating temp: -20° C to 40° C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- Up to 80% energy savings

INSTALLATION

- Licensed electrician required
- Contact Noribachi for additional support

WARRANTY

- 3-year manufacturer's warranty
- **5YR** - Optional 5-year manufacturer's warranty
- U.S. manufacturing and quality control

OPTIONS

- **IDR** - Internal Driver
- **EDR** - Remote Driver
- **CL** - Clear Lens
- **FL** - Frosted Lens

CERTIFICATIONS



LIGHT COLOR TEMPERATURE	MOUNTING
<ul style="list-style-type: none"> • CW - Cool White (5000K) • NW - Neutral White (4000K) • WW - Warm White (3000K) 	<ul style="list-style-type: none"> • Shunted and unshunted tombstones available upon request

ELECTRICAL CHARACTERISTICS

- Voltage: 120 - 277 V
- Frequency: 50 - 60 Hertz

NEW CONSTRUCTION OR RETROFIT

- Make any existing fluorescent lighting array LED
- Improve current lighting output, color, durability, and ambiance
- Features a wide beam angle, soft light and no glare

PRODUCT DETAILS

SIZE	WATTAGE	CCT	CATALOG NUMBER	LUMENS
4'	18W	5000K	T84 - CW - [LENS TYPE] - N - [DRIVER TYPE]	2,200 lm
			T84 - NW - [LENS TYPE] - N - [DRIVER TYPE]	2,100 lm
			T84 - WW - CL - N - [DRIVER TYPE]	2,000 lm
			T84 - WW - FL - N - [DRIVER TYPE]	1,980 lm

DIMENSIONS

