

Twist Lock Photocell

All products feature Noribachi's exclusive Bespoke Engineered and Specifically Tailored (BEST) manufacturing methodology.

CATALOG #:	TYPE:
PROJECT:	
COMMENTS:	DATE:
PREPARED BY:	

PRODUCT



Order Code: TLPC

Product Information

The twist lock photocell sensor (**TLPC**) features automatic on/off light control for outdoor LED lighting fixtures.

Specifications

- IP 65 Protection
- Built-In Surge Arrester
- Electromagnetic AC Relay Switching
- UV Stabilized Polycarbonate Cover and Clear Window
- High Impact Polybutylene Terephthalate Base
- 1" CdS Photocell
- 110J/3500A MOV
- Ambient Temp: -40°F ~ +158°F

Availability

- Arealight.R
- Arealight.S

WHEN APPROVED, THE SPECIFICATIONS OUTLINED IN THIS SPEC SHEET SHALL BECOME THE SPECIFICATION FOR THE MATERIAL TO BE DELIVERED BY NORIBACHI ON THE CITED PROJECT. AN AMENDED SPEC SHEET CAN BE PROVIDED BUT ONLY AFTER WRITTEN APPROVAL BY THE CUSTOMER IS RECEIVED. THIS DOCUMENT IS THE PROPERTY OF NORIBACHI AND CAN ONLY BE USED IN CONNECTION WITH MATERIALS FURNISHED BY NORIBACHI. ©2015