


RGBW Flood Light Comparison

Noribachi's BEST lighting solutions continue to outshine competitors.



Feature	<u>Noribachi</u>	<u>TPR Enterprises</u>	<u>Illuminarc</u>	<u>Color Kinetics</u>	<u>Coloronix</u>
	HBS.N 2X RGBW.252	Phantom 500W	Illumipanel 180IP	ColorReach Powercore	15-LED Flood Light
Lumens	19,920 lm	11,705 lm	10,823 lm	10,129 lm	2,232 lm
Lumens per in²	60.4 lm/in ²	35.5 lm/in ²	37.3 lm/in ²	17.1 lm/in ²	19 lm/in ²
Efficacy	80.3 LPW	27 LPW	20.3 LPW	41.6 LPW	32 LPW
Wattage	250 W	438 W	592 W	270 W	70 W
Optic	40 degree	45 degree	30 degree	43 degree	45 degree
Size (Length x Width)	27.5" x 12"	27.5" x 12"	29" x 10"	28.9" x 20.5"	12" Diameter
Weight	41 lbs	112 lbs	89 lbs	75 lbs	unknown
LEDs	252 LEDs	192 LEDs	180 LEDs	100 LEDs	15 LEDs
Mounting Options	Yoke bracket, Malleable hook, Handle, Pendant mount	Yoke bracket	Yoke bracket	Yoke bracket	Yoke bracket
IP Rating	IP67	IP65	IP67	IP66	IP65
DMX Connection Capability	Hardwired or wireless	Hardwired only	Hardwired only	Hardwired only	Hardwired only
LED Color Customization	Available	N/A	N/A	N/A	N/A
General Lighting Replacement	Yes	No	No	No	No
Fixture Customization	Available	N/A	N/A	N/A	N/A
Lead Time	4 - 6 weeks	12 weeks	12 weeks	12 weeks	12 weeks

All numbers were found on respective Manufacturers' website.