



# L-C-CUS-21-REC-B-CW-MT

NORIBACHI

## DETAILS

LIGHT COLOR TEMPERATURE
• CW - Cool White
MINIMUM GEOMETRY
• CIR - Circle

## ELECTRICAL CHARACTERISTICS

- Standard AC input: 120-277 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard

## LIGHT ENGINE RETROFITS

- L70 Rated life of 100,000+ hours
- Minimum CRI: 70
- Operating temp: -30° C to +60° C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- Eligible for Rebates
- 50-90% energy savings
- Manufactured in the USA

## AVAILABLE CONFIGURATIONS

DRIVE CURRENT	WATTAGE	DELIVERED LUMENS	ORDER CODE
B	37.8W	3,341lm	L-C-CUS-21-REC-B-CW-MT

## INSTALLATION

- Licensed electrician required
- Contact Noribachi for additional support

## WARRANTY

- 5-year manufacturer's warranty
- 10YR - Optional 10-year manufacturer's warranty
- U.S. manufacturing and quality control

## ORDERING INFO

- For sales and support, contact [sales@noribachi.com](mailto:sales@noribachi.com) or 855.283.1100.

## NEW CONSTRUCTION OR RETROFIT

- Make any existing lighting array LED
- Seamlessly integrate an LED light engine retrofit into any fixture intended for metal halide, fluorescent, or induction
- Improve current lighting output, color, durability, and ambiance

## CERTIFICATIONS

