



L-C-CUS-60-REC-A-CW-MT

DETAILS

LIGHT COLOR TEMPERATURE
• CW – Cool White
MINIMUM GEOMETRY
• REC – Rectangle

ELECTRICAL CHARACTERISTICS

- Standard AC input: 120-277 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.92
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard

LIGHT ENGINE RETROFITS

- L70 Rated life of 100,000+ hours
- CRI: 71
- CCT: 5289 K
- Efficacy (lm/W): 89.49
- Operating temp: -30° C to +60° C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- Eligible for Rebates
- 50-90% energy savings
- Manufactured in the USA

AVAILABLE CONFIGURATIONS

DRIVE CURRENT	WATTAGE	DELIVERED LUMENS	ORDER CODE
350mA	70W	6,218lm	L-C-CUS-60-REC-A-CW-MT

INSTALLATION

- Licensed electrician required
- Contact Noribachi for additional support

WARRANTY

- 5-year manufacturer's warranty
- U.S. manufacturing and quality control

ORDERING INFO

- For sales and support, contact sales@noribachi.com or 855.283.1100.

CERTIFICATIONS

