



# ZIP – 138 – [optional upgrades]

## DETAILS

<b>LIGHT COLOR TEMPERATURE</b>
<ul style="list-style-type: none"> <li>CW – Cool White</li> </ul>
<b>MINIMUM GEOMETRY</b>
<ul style="list-style-type: none"> <li>REC - Rectangle</li> </ul>

## ELECTRICAL CHARACTERISTICS

- Standard AC input: 120-277 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.937
- Total harmonic distortion: 12.2%
- Surge protection: IEC/EN 61000-4-5 EMC test standard

## LIGHT ENGINE RETROFITS

- L70 Rated life of 100,000+ hours
- CRI: 72.9
- CCT: 5166 K
- Efficacy (lm/W): 106.2
- Operating temp: -30° C to +60° C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- Eligible for Rebates
- 50-90% energy savings
- Manufactured in the USA

## AVAILABLE CONFIGURATIONS

<b>DRIVE CURRENT</b>	<b>WATTAGE</b>	<b>DELIVERED LUMENS</b>	<b>ORDER CODE</b>
535mA	222.06W	23,582.72lm	ZIP – 138 – [optional upgrades]

## INSTALLATION

- Licensed electrician required
- Contact Noribachi for additional support

## WARRANTY

- 5-year manufacturer’s warranty
- U.S. manufacturing and quality control

## ORDERING INFO

- For sales and support, contact [sales@noribachi.com](mailto:sales@noribachi.com) or 855.283.1100.

## CERTIFICATIONS

