



DETAILS

LIGHT COLOR TEMPERATURE	
• CW - Cool White	
MINIMUM GEOMETRY	
• REC - Rectangular - 8" X 7.5"	
• ROU - Round - 9"	

ELECTRICAL CHARACTERISTICS

- Standard AC input: 120-277 VAC
- EMI filter: 47CFR, part 2, part 15
- Power factor: >.9
- Total harmonic distortion: <20%
- Surge protection: IEC/EN 61000-4-5 EMC test standard

LIGHT ENGINE RETROFITS

- L70 Rated life of 100,000+ hours
- Minimum CRI: 70
- Operating temp: -30° C to +60° C
- No toxic chemicals/ROHS compliant
- ETL certified, meets UL and CSA standards
- Eligible for Rebates
- 50-90% energy savings
- Manufactured in the USA

AVAILABLE CONFIGURATIONS

WATTAGE	LUMEN OUTPUT	ORDER CODE
144.3W	15,001lm	ZIP - 084 - [optional upgrades]

OPTIONAL UPGRADES

- OS - Occupancy Sensor
- PC1 - 120V Button Photocell
- PC2 - 240V Button Photocell
- DHS - Daylight Harvesting Sensor
- SRG1 - Enhanced surge protection for 120-277VAC
- L515 - L515P 120V Twist Lock Plug
- L615 - L615P 240V Twist Lock Plug
- L715 - L715P 277V Twist Lock Plug
- L720 - L720P 277V Twist Lock Plug
- CORD6 - 6' 16/3 600V STW Cord
- WET - Wet Rating
- EM - Emergency Battery Backup
- EMC - Emergency Battery Backup Cold

WARRANTY

- 5-year manufacturer's warranty
- 10YR - Optional 10-year manufacturer's warranty
- U.S. manufacturing and quality control

INSTALLATION

- Licensed electrician required
- Contact Noribachi for additional support

NEW CONSTRUCTION OR RETROFIT

- Make any existing lighting array LED
- Seamlessly integrate an LED light engine retrofit into any fixture intended for metal halide, fluorescent, or induction
- Improve current lighting output, color, durability, and ambiance

ORDERING INFO

- For sales and support, contact [sales@noribachi.com](mailto:sales@noribachi.com) or 855.283.1100.

CERTIFICATIONS

